

PART # 11309 - - 1955 - 56 - 57

2DR Hardtop Tack Strip

Instruction Sheet

Revised 1/2011



This 11309 Tack Strip Kit is designed to replace the missing or old tack strips. You will be able to install your New Headliner and Attach the Windlace at rear of door, back to new condition.

11309 Kit Includes:

1 - Top of Windshield	50" Long and 1/8" Thick
1 - Top of Back Glass	60" Long and 1/8" Thick
2 - Top of Side Windows	63" Long and 3/8" Thick
2 - Top of Rear Door Openings	9" Long and 1/8" Thick
2 - Bottom of Rear Door Openings	16" Long and 3/8" Thick


Headliner Area

1. Remove old tack strip. Some locations the tack strip is held in place tabs (See View C below). Carefully bend tabs to release tack strips. Once all are removed clean surface.
2. Fit the new Tack Strips into place, see diagrams below to install them in the correct locations.
3. To help hold Tack Strips in use a small amount of a high-tach cement on the back side of strips. Carefully push down the tabs.
4. In some cases you will need to drill a hole through the Tack Strip and Body of Car to attach Strips. It is best to pop-riquet to hold them in place. A small screw can be used.
5. Follow the instructions in the Body Section 1-1 of your Shop Manual, 522 for 1955, 523 for 56, and 524 for 1957. This information can also be found in the Body By Fisher Service News, our part numbers 992, 1116 and 1117.


Door Panel Area

1. Remove old tack strip. Some locations the tack strip is held in place tabs. Carefully bend tabs to release tack strips. Once all are removed clean surface.
2. Fit the new Tack Strips into place, see Door Windlace Diagram below to install them in the correct locations.
3. To help hold Tack Strips in use a small amount of a high-tach cement on the back side of strips. Carefully push down the tabs. Drill a hole through the Tack Strip and Body of Car to attach Strips. It is best to pop-riquet them in place.

1955 Headliner



1956-57 Headliner



Door Windlace

